

PATENT COOPERATION TREATY

From the INTERNATIONAL BUREAU

PCT

NOTIFICATION CONCERNING
TRANSMITTAL OF COPY OF INTERNATIONAL
APPLICATION AS PUBLISHED OR REPUBLISHED

To:

MODIANO, Guido
Modiano & Associati
Via Meravigli, 16
20123 Milano
ITALIE

Date of mailing (*day/month/year*)
17 February 2005 (17.02.2005)

Applicant's or agent's file reference
39407/GM/ps

IMPORTANT NOTICE

International application No.
PCT/EP2004/008334

International filing date (*day/month/year*)
26 July 2004 (26.07.2004)

Priority date (*day/month/year*)
01 August 2003 (01.08.2003)

Applicant
OMETTO, Walter et al

The International Bureau transmits herewith the following documents:

- ☒ copy of the international application as published by the International Bureau on 17 February 2005 (17.02.2005) under No. WO 2005/013743
- ☐ copy of international application as republished by the International Bureau on under No. WO
- For an explanation as to the reason for this republication of the international application, reference is made to INID codes (15), (48) or (88) (*as the case may be*) on the front page of the attached document.

The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Authorized officer

Agnes Wittmann-Regis

Facsimile No.+41 22 740 14 35

Facsimile No.+41 22 338 89 70

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)


PCT

(10) International Publication Number
WO 2005/013743 A1

- (51) International Patent Classification⁷: A43B 7/06, 13/20
- (21) International Application Number:
PCT/EP2004/008334
- (22) International Filing Date: 26 July 2004 (26.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PD2003A000176 1 August 2003 (01.08.2003) IT
- (71) Applicants and
(72) Inventors: OMETTO, Walter [IT/IT]; Corso Milano, 94, I-35139 Padova (IT). MOCAVERO, Anna, Maria [IT/IT]; Via Bellavitis, 13, I-35127 Padova (IT).
- (74) Agent: MODIANO, Guido; Modiano & Associati, Via Meravigli, 16, 20123 Milano (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SHOE WITH FOOT MASSAGING SOLE



(57) Abstract: A shoe (10) comprising a sole (12) which is provided, in its heel (13), with a tank (14) in which pressurized air is accumulated by means of a pump (15) actuated by the heel of the foot during normal walking. The shoe is provided with a foot supporting insole (33), which is provided with a plurality of holes (32) in which a plurality of studs (31) move at right angles to the ground; the studs are associated with an elastic chamber (22, 23, 24), which is connected to the air tank with the interposition of a discharge valve (18), which acts when the pressure inside the tank has reached a preset value; the studs accordingly act impulsively against the sole of the foot at preset intervals.



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SHOE WITH FOOT MASSAGING SOLE

Technical Field

The present invention relates to a shoe with foot massaging sole.

Background Art

5 It is known that the foot has nerve endings that are connected to all the organs of the body, so that by acting with localized pressures it is possible to act so as to prevent or treat disorders that in particular cause painful states.

10 The technique of foot treatment has been known since antiquity and has been, and still is, widely used.

When there were no drugs for treating diseases, disorders or affections of various kinds, man sought natural remedies that could provide relief.

15 These means were found by instinct in a manipulation of the painful regions, developing a search for points that acted by reflex on the painful region.

It was thus discovered gradually that terminations, subsequently defined as nerve endings, were concentrated in the foot and, if stimulated, could transfer the stimulus to other organs of the body.

20 A reflex is an involuntary but so to speak automatic response to a stimulus that causes excitation of a sensitive neuron that transmits its action up to the cerebral level.

Every part of the body is a locus of these reflexes, but more active regions are present in the foot.

25 Figure 1 is a view of a sole of a foot, divided into four regions designated by the reference numerals A, B, C and D.

Region A contains the endings linked in particular to teeth, lymphatic circulation, eyes and ears; region B contains the endings linked to the gallbladder, liver, heart, bronchi, thyroid, and stomach; region C contains
30 the endings linked to the intestine, colon, kidneys, vertebrae; and region D

contains the endings linked to the genitalia, to the meniscus and to the legs.

By stimulating one of these points, it is possible to have a beneficial effect on the various organs, as demonstrated by many medical studies in reflexology and zone massage.

5 Shoes are known which have a foot supporting insole provided with protrusions in various regions or constituted by a mat of small studs of various hardness.

In this case, this is a passive means, which produces a sort of massage whenever, by resting the foot, the sole of the foot bears onto the protrusions
10 or on the studs.

The action is very limited, and for some sensitive individuals resting the foot on an insole with many protrusions is unpleasant or even painful.

Disclosure of the Invention

The aim of the present invention is to provide a shoe that massages
15 the foot actively.

Within this aim, an object of the present invention is to provide a sole in which it is possible to adjust the massaging means by choosing the points of the foot to be affected.

Another object of the invention is to provide a sole in which it is
20 possible to adjust the intensity of the massage and also deactivate it.

A further object is to provide a sole that can be applied to any type of shoe.

A still further object is to provide a sole with active massage means that do not require energy supply sources that deplete.

25 Another object is to provide a massaging sole in which said massaging means also provide internal ventilation.

Another object is to provide a massaging sole whose components are structurally simple and have a low cost.

This aim and these and other objects that will become better apparent
30 hereinafter are achieved by a shoe with foot massaging sole, characterized

in that it comprises a tank, which is located preferably within the heel of the shoe sole, and a pump, which is located below the heel of the foot and is actuated by said heel of the foot while walking, said pump introducing air in said tank, which gradually increases its internal pressure, an air discharge
5 duct branching out from said tank, an adjustable valve being interposed along said air discharge duct and opening when a preset pressure is reached, said valve feeding at least one elastic chamber provided with a plurality of studs, which are directed toward the sole of the foot and are inserted in corresponding holes provided in a foot supporting insole; said studs, when
10 the air is discharged, protruding from said holes and acting on the sole of the foot, said outflowing air being conveyed, preferably by means of a tube, into the shoe and producing an internal ventilation.

Brief description of the Drawings

Further characteristics and advantages of the present invention will
15 become better apparent from the following detailed description of some embodiments thereof, illustrated by way of non-limiting example in the accompanying drawings, wherein:

Figure 1 is a plan view of the sole of a foot, divided into regions of different sensitivity;

20 Figure 2 is a longitudinal sectional view of the shoe according to the invention;

Figure 3 is a sectional view of some of the parts that compose the sole;

25 Figure 4 is an exploded perspective view of the parts that compose the sole;

Figure 5 is a sectional view of a part of the sole, illustrating the studs in the inactive condition;

Figure 6 is a sectional view of the sole of Figure 5, in which the studs protrude from the insole due to the pressure of the air;

30 Figure 7 illustrates, at the top, the chart of the increase in the air

pressure in the tank and of the discharge of said air from said tank, and, at the bottom, the pulsed pressure that acts on the studs.

Ways of carrying out the Invention

With reference to the figures cited in the introduction of the present
5 description, Figure 1 has already been discussed.

With reference to Figures 2 and onward, a shoe, generally designated by the reference numeral 10, is composed of an upper 11, which is associated with a tread sole 12 provided with a heel 13.

A tank 14 is contained in the heel 13, and a pump 15, for example of
10 the membrane type covered by a deformable insole 16, is provided above said tank.

Every time the pump 15 is compressed by the heel of the foot, and this occurs at each step, it introduces air in the tank 14.

Conveniently, the air can be drawn from the outside of the shoe, so as
15 to be changed constantly.

It is in any case possible to draw the air contained in the shoe, although this does not produce air change.

The tank 14 is provided with a discharge duct 17, which is controlled by an adjustable valve 18.

20 The adjustable valve 18, in the case shown in Figure 4, has three outputs, and it is possible to select one or two or all of them by rotating for example a ring.

The valve 18 is also adjustable in terms of pressure, i.e., it opens at a chosen pressure when said pressure is reached inside the tank 14.

25 With reference to Figure 4, the three outputs, designated by the reference numerals 19, 20 and 21, are connected to three elastic chambers, designated by the reference numerals 22, 23 and 24 respectively, which are located, in the case shown, at the regions A, B and C of the sole of the foot, shown in Figure 1.

30 Each one of the elastic chambers 22, 23 and 24 is provided with a

discharge tube, designated by the reference numerals 25, 26 and 27 respectively; said tubes merge into a single additional tube 28, which preferably leads into the inside of the shoe 10.

The elastic chambers 22, 23 and 24 are constituted, as shown more clearly in Figures 5 and 6, which illustrate by way of example the elastic chamber 23, by a bag made of an elastic material, which is provided with a lower wall 29 and with an upper wall 30.

The upper wall 30 has a plurality of studs 31 that protrude upward, i.e., toward the inside of the shoe 10.

10 The studs 31 are located at a plurality of holes 32, which are provided in a foot supporting insole 33 that is superimposed on the elastic chambers 22, 23 and 24.

Each hole 32 has a taper 34, with the larger end downward, which allows, as shown in Figure 6, the elastic deformation of the upper wall 30 under the effect of the pressure of the internal air, so that the studs 31 exit from the holes 32, pressing in an impulsive manner against the sole of the foot.

Figure 7 illustrates two charts: the upper chart 35 plots the pressure of the air inside the tank 14, and the lower chart 36 plots the pressure inside the elastic chambers 22, 23 and 24.

In the tank 14, the pressure rises in steps 37, each of which corresponds to the compression of the heel, at each stride, on the pump 15.

The impulsive discharge of the tank 14, shown by the descending ramp 39, occurs once the pressure P1, which is designated by the reference numeral 38 and is the pressure set on the valve 18, has been reached.

Correspondingly, an impulsive pressure, designated by the reference numeral 40 in the chart 36, is generated inside the elastic chambers 22, 23 and 24 and pushes the studs 31 upward and therefore against the sole of the foot in the chosen region.

30 In this manner, the aim is achieved of having a foot massage obtained

in a manner that is active and not passive and is also adjustable.

The valve, which has been described with single-pulse discharge, can be of the sequential type, i.e., once a preset pressure is reached, the discharge occurs by means of a plurality of consecutive pulses until a low
5 pressure that retriggers its closure is reached.

Such valve has a position in which it remains constantly open, and in this manner it is possible to exclude the foot massaging action completely.

Downstream of the valve it is possible to arrange a small tank, which contains fragrancing or sanitizing products to be replenished periodically.

10 These products are introduced in the shoe whenever the air that actuates the studs is discharged.

It is also possible to provide a further elastic chamber, which is arranged around the pump in the heel region, so as to also achieve massage of the part D, shown in Figure 1.

15 The pump can be a multiple pump, and the tank can be divided into as many parts as there are pump sections.

In this case, with a plurality of adjustable valves, it is possible to have a different action on the various parts of the sole of the foot.

From what has been described and shown, it is evident that all the
20 intended aim and objects have been achieved, and that in particular a sole has been obtained which allows to obtain a foot massage in the chosen manner and with an adjustable action that the wearer of the shoe can thus choose according to his sensitivity.

The combined massaging and internal ventilation action allows to
25 achieve an optimum condition for the foot and therefore a feeling of wellbeing for the wearer of the shoe.

It is obvious that starting from the same inventive concept, the sole can be provided in various manners and with various kinds of material, depending on the quality of the shoe to be provided.

30 The disclosures in Italian Patent Application No. PD2003A000176

from which this application claims priority are incorporated herein by reference.

CLAIMS

1. A shoe with foot massaging sole, characterized in that it comprises a tank, which is located within the shoe sole, and a pump, which is located below the heel of the foot and is actuated by said heel of the foot while walking, said pump introducing air in said tank, which gradually increases its internal pressure, an air discharge duct branching out from said tank, an adjustable valve being interposed along said air discharge duct and opening when a preset pressure is reached, said valve feeding at least one elastic chamber provided in an upper region, i.e., toward the sole of the foot, with a plurality of studs, which are inserted in corresponding holes provided in a foot supporting insole, said studs, when the air is discharged, protruding from said holes and acting on the sole of the foot, said outflowing air being conveyed, preferably by means of a tube, into the shoe and thus producing an internal ventilation.
2. The shoe according to claim 1, characterized in that said pump is of the membrane type, is arranged within the heel of the shoe and is covered by a deformable insole on which the heel of the foot acts.
3. The shoe according to claim 1, characterized in that said pump is of the piston type.
4. The shoe according to claim 1, characterized in that said valve that controls the output duct of the tank is adjustable to a chosen pressure within a range between atmospheric pressure and the safety pressure of the tank.
5. The shoe according to claim 1, characterized in that said valve has a single output if the sole has a single elastic chamber.
6. The shoe according to claim 1, characterized in that said valve has a plurality of outputs, i.e., one for each one of the elastic chambers, when more than one elastic chamber is provided.
7. The shoe according to claims 1 and 6, characterized in that in the case of a plurality of elastic chambers with said valve a single elastic chamber is selectable into which the air is discharged or a plurality of

elastic chambers are selectable into which the air is discharged simultaneously.

8. The shoe according to claims 1 and 6, characterized in that said valve discharges the air sequentially into the elastic chambers.

5 9. The shoe according to claim 1, characterized in that said valve is of the type with discharge performed by a plurality of consecutive pulses.

10. The shoe according to claim 1, characterized in that said elastic chamber is constituted by a bag made of elastic material, said bag having, on its upper wall directed toward the sole of the foot, a plurality of studs, 10 which are inserted in corresponding holes provided in a supporting insole interposed between said elastic chamber and the sole of the foot.

11. The shoe according to claims 1 and 9, characterized in that in the inactive condition said studs do not protrude from said foot supporting insole, while when the air pressure pulse occurs said studs protrude from 15 said holes.

12. The shoe according to claim 1, characterized in that said holes provided in the foot supporting insole have a frustum-like shape, with an upper end whose diameter is substantially equal to the diameter of the stud and a lower end that is much wider in order to allow the elastic deformation, 20 under pressure, of the upper wall of the elastic chamber, with simultaneous protrusion of the studs from said foot supporting insole.

13. The shoe according to claim 1, characterized in that in a point affected by the passage of the air during discharge, a refillable tank is provided that contains fragrancings and/or sanitizing products, which are 25 conveyed by the air into the shoe at each discharge.

14. The shoe according to claim 1, characterized in that said pump draws air from the outside of the shoe.

15. The shoe according to claim 1, characterized in that said pump draws air from the inside of the shoe.

30 16. The shoe according to claim 1, characterized in that the air that

exits from the elastic chamber or chambers is discharged outside the shoe.

17. The shoe according to claim 1, characterized in that said pump is composed of multiple pump, each of the individual pumps feeding a single tank, each one of said tanks being provided with an adjustable valve, each
5 one of said valves supplying at least one elastic chamber.

18. The shoe according to claim 1, characterized in that said elastic chamber is an elastic tube with a preset path under the foot supporting insole.





Fig. 1



3/5








Fig. 3

4/5



5/5



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP2004/008334

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A43B7/06 A43B13/20

According to International Patent Classification: (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A43B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search forms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 01/03536 A (KIM JOO TAE) 18 January 2001 (2001-01-18) page 7, line 8 - page 10, line 8; figures 7-12	1
A	EP 0 903 984 A (BRUE S P A) 31 March 1999 (1999-03-31) paragraph '0017! - paragraph '0020!; figures 3,6	1
A	US 4 446 634 A (JOHNSON PAUL H ET AL) 8 May 1984 (1984-05-08) the whole document	1
A	DE 202 06 885 U (WU CHIEN I) 18 July 2002 (2002-07-18) the whole document	1
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

25 November 2004

Date of mailing of the international search report

03/12/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vesin, S

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2004/008334

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0103536	A	18-01-2001	KR 164116 Y1	15-02-2000
			KR 201935 Y1	01-11-2000
			KR 200030 Y1	16-10-2000
			AU 5575600 A	30-01-2001
			CN 1279919 A	17-01-2001
			EP 1202644 A1	08-05-2002
			WO 0103536 A1	18-01-2001
EP 0903984	A	31-03-1999	IT MI961027 A1	24-11-1997
			AT 195226 T	15-08-2000
			DE 69702758 D1	14-09-2000
			DE 69702758 T2	12-04-2001
			EP 0903984 A1	31-03-1999
			GR 3034729 T3	31-01-2001
			HK 1018930 A1	11-05-2001
			JP 2000510741 T	22-08-2000
			US 6076282 A	20-06-2000
			CA 2255557 A1	27-11-1997
			CN 1219107 A	09-06-1999
			WO 9743918 A1	27-11-1997
			ES 2150256 T3	16-11-2000
			ID 17379 A	24-12-1997
			KR 2000015884 A	15-03-2000
			PT 903984 T	31-01-2001
US 4446634	A	08-05-1984	NONE	
DE 20206885	U	18-07-2002	GB 2386538 A	24-09-2003
			US 2003188451 A1	09-10-2003
			DE 20206885 U1	18-07-2002
US 4047310	A	13-09-1977	NONE	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2004/008334

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0103536	A	18-01-2001	KR 164116 Y1 KR 201935 Y1 KR 200030 Y1 AU 5575600 A CN 1279919 A EP 1202644 A1 WO 0103536 A1	15-02-2000 01-11-2000 16-10-2000 30-01-2001 17-01-2001 08-05-2002 18-01-2001
EP 0903984	A	31-03-1999	IT MI961027 A1 AT 195226 T DE 69702758 D1 DE 69702758 T2 EP 0903984 A1 GR 3034729 T3 HK 1018930 A1 JP 2000510741 T US 6076282 A CA 2255557 A1 CN 1219107 A WO 9743918 A1 ES 2150256 T3 ID 17379 A KR 2000015884 A PT 903984 T	24-11-1997 15-08-2000 14-09-2000 12-04-2001 31-03-1999 31-01-2001 11-05-2001 22-08-2000 20-06-2000 27-11-1997 09-06-1999 27-11-1997 16-11-2000 24-12-1997 15-03-2000 31-01-2001
US 4446634	A	08-05-1984	NONE	
DE 20206885	U	18-07-2002	GB 2386538 A US 2003188451 A1 DE 20206885 U1	24-09-2003 09-10-2003 18-07-2002
US 4047310	A	13-09-1977	NONE	

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2004/008334

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 047 310 A (SUNOO HYENG P) 13 September 1977 (1977-09-13) the whole document -----	1

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.